












	Product Photos and Exhibitor Information	Product Description
1	 <p>IGBT Modules HY Electronic (Cayman) Limited (Taiwan) Booth No.: 5F-C20</p>	<ul style="list-style-type: none"> - Applications: inverter for motor drive, AC and DC servo drive amplifier, uninterruptible power supply - Covers 10A to 15A with voltage ranging from 600V to 1200V, suitable for applications in inverters, servers, and welding machine areas
2	 <p>Motion Control LSI Kyopal Co., Ltd. (Japan) Booth No.: 5F-E17</p>	<ul style="list-style-type: none"> - A pulse generator LSI - Controls speed and position of server motors with pulse train and stepping motors - Professionally engineered and requires little maintenance
3	 <p>Neutek International HK Limited (Hong Kong) Booth No.: 5G-A26</p>	<ul style="list-style-type: none"> - A simple, low cost and highly secured anti-counterfeiting technology - The encrypted pattern on the label has the following unique features: - Pattern disappears after smearing with water or by marker pen but re-appear after drying with tissue paper - The pattern would stay on the aluminium layer which cannot be removed

	Product Photos and Exhibitor Information	Product Description
4	 <p data-bbox="292 510 678 683">Super Thin SMD Display Opto Plus LED Corporation (Taiwan) Booth No.: 5F-D11</p>	<ul data-bbox="754 185 1425 501" style="list-style-type: none"> - Application: Home Appliance (White Goods) - Plastic housing height of 1.01mm only and can be light up without spot - Specially designed for reverse mounting on glass for touch screen application to save glass cost - Can be driven 105°C
5	 <p data-bbox="268 1261 702 1435">PST-360 Through-shaft Sensor Piher Sensors & Controls S.A. (Spain) Booth No.: 5F-E19</p>	<ul data-bbox="754 703 1425 1167" style="list-style-type: none"> - Application: off-road, industrial, material handling, agricultural vehicles and marine equipment - A non-contacting technology that senses the shafts' position over 360 degrees with accuracy up to +/- 0.5% - 50 million rotation cycles - Varies output protocols (analogue, PWM and SPI) - Fully sealed protection (IP67)

	Product Photos and Exhibitor Information	Product Description
6	 <p data-bbox="268 555 702 734">LED Driver PREMA Semiconductor GmbH (Germany) Booth No.: 5F-D06</p>	<ul style="list-style-type: none"> - Application: Retrofit lamps (buck converter & dimming), torches (boost converter; low to high power), automatic garden lamps, LCD backlighting, OLED driver - Offers appropriate products and superior service integrate the LED driver into the product - Next to variety of standard products (ASSP), PREMA develops ASICs to fabricate (copy-protected) LED drivers as required
7	 <p data-bbox="296 1205 673 1339">Prokit's Industries Co., Ltd (Taiwan) Booth No.: 5F-E23</p>	<p data-bbox="753 795 1276 828">4-in-1 Fiber Optical Power Multimeter</p> <ul style="list-style-type: none"> - Application: Fiber optics - Powerful functions include: <ol style="list-style-type: none"> 1. "FIBER OPTICAL POWER METER": Wide range of power measurement from 850nm to 1625nm; 2. "VISUAL FAULT LOCATOR": Easy to locate the breakpoint and bad connections in fiber optic cables 3. "CABLE TESTER": Test pin to pin cable map indicator (1~8 LEDs); 4. "LED FLASHLIGHT": Features 2 modes for long illumination and SOS signal

	Product Photos and Exhibitor Information	Product Description
8	 <p data-bbox="284 577 686 824"> Mini Aluminium TRI-STEPTM PSM Fasteners (Hong Kong) Limited (Hong Kong) Booth No : 5G-B30 </p>	<ul style="list-style-type: none"> - A unique three stepped threaded insert and mating hole combination, designed for heat installation into thermoplastic materials - The design incorporates two diameters of opposing helical knurls and a series of annular vanes, advantages include: <ol style="list-style-type: none"> 1. High pull-out and direct torque performance. 2. A large clearance between the vane and top hole diameter, equivalent to tapered inserts 3. Excellent location, eliminating misalignment during installation 4. Increased surface contact area giving greater resistance to a torque induced “jack-out” 5. Aluminum versions give a 66% weight reduction and insertion process cost savings
9	 <p data-bbox="295 1377 678 1556"> 3D Tile Format S.I.SV.EL. (Hong Kong) Ltd (Hong Kong) Booth No.: 5F-G02 </p>	<ul style="list-style-type: none"> - The 3D tile format enables delivery of HD 3D content with a higher quality than current solutions and allows broadcasters to transmit a single video service for 2D and 3D audiences. - Guarantees consumers with traditional 2D TV sets can still enjoy the service in 2D format - Integrates storage of two stereoscopic 720p frames into a single 1080p frame - Allows resolution of the source stream to be maintained with strong bandwidth efficiency and picture quality

	Product Photos and Exhibitor Information	Product Description
10	<p>Quad-HD display(1440*2560)</p>  <p>Normal display(720*1280)</p> <p>2K Display Module Truly Semiconductors Ltd (Hong Kong) Booth No.: 5F-F02</p>	<ul style="list-style-type: none"> - With a resolution of Quad-HD (1440*2560), Truly's 2K display module provides four times sharper display performance than HD720 - It could offer better display performance for picture, text and video
11	 <p>Ultra Narrow-border & Borderless OGS Truly Semiconductors Ltd (Hong Kong) Booth No.: 5F-F02</p>	<ul style="list-style-type: none"> - Improves the appearance of phone and creates higher screen-front panel ratio - Larger and wider vision experience - Adopting the ITO route technology enables the non-border effect of touch panel module